

A136, A236



TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor or single phase as option, placed into a protective housing
- Electric cable 10m long with industrial plug 3Ph+T 16A
- Vacuum meter to control filter efficiency
- Machine body Ø360mm
- Manual filter shaker on top
- Star filter of polyester cat. "L"
- Quick inlet Ø70mm
- Waste bin of 25 l with handles, removable
- Rear castors Ø125mm, front castor Ø100mm with

brake

- Painted version with frame, container and filter chamber in Ral 9003 (white)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- X3 version all of stainless steel

		A136	A236
Tension/ Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	0,9	1,5
Depression max	mbar max	230	250
Max working depression	mbar	150	210
Max air flow	m ³ /h	150	210
Primary filter surface	m ²	0,70	0,70
Upstream absolute filter	m ²	NO	NO
Downstream absolute filter	m ²	4,8	4,8
Cartridge filter surface	m ²	NO	NO
Container capacity	Lt	25	25
Product inlet	mm	Ø70	Ø70
Noise level	DbA	70	64
Overall dimensions	Cm	40X70X126h	40X70X126h
Weight	Kg	69	71
Protection	IP	55	55