

A21_{LU}MX1.3D



TECHNICAL FEATURES:

- Machine body Ø360mm
- Side channel blower with single phase motor asynchronous marked ATEX EX II 3D
- Vacuum-meter to check filter efficiency
- Electric cable 10mt long with industrial plug 2P+earth 16A IP67 marked ATEX
- Manual filter shaker on side
- Star filter in polyester class “L” antistatic
- Quick inlet Ø70mm
- Relief valve put in as standard
- Container of 25 Lt with handle and castors, in stainless steel
- Rear castors Ø125mm, front castors Ø100mm with brake, antistatic version
- Standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 9003 white
- X2 version with container and filter chamber in stainless steel
- X3 version completely in stainless steel
- We recommend the use of suction accessories Ø40mm

		A21PMX1.3D
Tension /Voltage	Volts	1~ 230V/50Hz
Plug	A	2P + T 16A IP67
Power	kW	1.5
Depression max	mbar	200
Max air flow	m ³ /h	200
Primary filtering surface	m ²	1,14
Absolute filtering surface	m ²	1,20
Container capacity	Lt	25
Product inlet	mm	Ø70
Noise level	dB(A)	67
Overall dimensions	Cm	47X61X135h
Weight	Kg	60
Protection	IP	65
EX Marking	EX	II3D T135 °C