

F230



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor three phase or in option single phase, placed into a protective housing
- Electric cable 10m long with industrial plug 3Ph+ T 16A
- Vacuum meter to control the filter efficiency
- Body of the machine Ø360mm
- Manual filter shaker on top
- Star filter of polyester cat. "L"
- Quick inlet Ø70mm
- Waste bin of 25 l with handles, removable
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with fram, waste bin and filter cahmber Ral 9003 (white)
- X1 version with container in stainless steel
- X2 versione with container and filter chamber in stainless steel
- X3 version with waste bin, filter chamber and frame in stainless steel
- Quick installation of all options

		F230
Tension /Voltage	Volts	230-400V/50Hz
Power	Kw	1,5
Depression Max	mbar max	250
Working Depression	mbar	210
Max air flow	m ³ /h	210
Primary filter surface	m ²	0,70
Upstream absolute filter	m ²	1.55
Downstream absolute filter	m ²	4,8
Cartridge filer surface	m ²	NO
Container capacity	Lt	25
Product inlet	mm	Ø70
Noise level	DbA	64
Overall dimensions	Cm	40X70X151h
Weight	Kg	90
Protection	IP	55