

## F340



### TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor, placed into protective housing
- Electric cable 10m long with industrial plug 3Ph+ Earth 16A
- Vacuum-meter to monitor the filter efficiency
- Machine body Ø460mm
- Manual filter shaker on top
- Star filter of polyester cat. "L"
- Quick inlet Ø70mm
- Dust bin of 48 l. with handles, removable
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with frame, dust bin and filter chamber in painted steel RAL 9003 (white)
- X1 version with dust bin in stainless steel
- X2 version with dust bin and filter chamber in stainless steel
- X3 version with dust bin, filter chamber and frame in stainless steel
- Easy installation of options and accessories

		F340
Tension / Voltage	Volts	230-400V/50Hz
Power	Kw	2.2
Max depression	mbar max	310
Max working depression	mbar	200
Max air Flow	m <sup>3</sup> /h	310
Primary filter surface	m <sup>2</sup>	1,90
Upstream absolute filter	m <sup>2</sup>	2,2
Downstream absolute filter	m <sup>2</sup>	4,8
Cartridge filter kit	m <sup>2</sup>	5
Container capacity	Lt	48
Product inlet	mm	Ø70
Noise level	DbA	73
Overall dimensions	Cm	50X80X154h
Weight	Kg	120
Protection	IP	55